



Declaration of Performance

1. Unique identification code of the product-type:

Novia 500 Gauge Virgin Grade Vapour Control Layer

2. Product style:

2.7m x 50m, presented centre folded

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:

Flexible sheets for waterproofing – Plastic and rubber vapour control layers – Definitions and characteristics (BS EN 13984)

4. Name and contact address of the manufacturer:

Novia Ltd
Unit 3 Trilogy
Eurolink V Industrial Park
Sittingbourne
Kent
ME10 3NH

5. System of assessment and verification of constancy of performance of the construction product:

System 3

6. Approved body:


British Board of Agreement (BBA) – AB 0836



7. Declared Performance:

Essential Characteristics	Technical Performance	Bottom Tolerance	Top Tolerance	Unit	Test Standard
Length	50	50	55	m	BS EN 1848-2
Width	2.7	2.63	2.77	m	BS EN 1848-2
Thickness	0.125	0.109	0.141	mm	BS EN 1849-2
Mass per unit area (weight)	115	100.6	129.4	g/m ²	BS EN 1849-2
Tensile strength MD:CD	>101:>93	-	-	N/50mm	BS EN 12311-2
Nail tear resistance MD:CD	>65 : > 65	-	-	N	BS EN 12310-1
Water vapour transmission properties	0.68	0.48	0.88	g/m ² .day	BS EN 1931
Water tightness at 2kPa	PASS	-	-	-	BS EN 1928

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. The product stated at point 1 conforms to declared performances at point 7.


.....
Adrian Chisholm, Managing Director
Novia Ltd, Sittingbourne, Kent, UK

.....01.12.2022.....
Date