

Declaration of Performance

1. Unique identification code of the product-type:

Novia 1200 Gauge Virgin Grade Vapour Control Layer

2. Product style:

4m x 25m, presented M-folded

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:

Flexible sheets for waterproofing – Plastic and rubber vapour control layers – Definitions and characteristics (BS EN 13984)

4. Name and contact address of the manufacturer:

Novia Ltd Unit 3 Trilogy Eurolink V Industrial Park Sittingbourne Kent ME10 3NH

5. System of assessment and verification of constancy of performance of the construction product:

System 3

6. Approved body:

British Board of Agrement (BBA) - AB 0836



7. Declared Performance:

Essential Characteristics	Technical Performance	Bottom Tolerance	Top Tolerance	Unit	Test Standard
Length	25	25	27.5	m	BS EN 1848-2
Width	4	3.9	4.1	m	BS EN 1848-2
Thickness	0.3	0.263	0.338	mm	BS EN 1849-2
Mass per unit area (weight)	265	232	298	g/m ²	BS EN 1849-2
Tensile strength MD:CD	>129 :>110	-	-	N/50mm	BS EN 12311-2
Nail tear resistance MD:CD	>102:>102	-	-	N	BS EN 12310-1
Water vapour transmission properties	0.27	0.19	0.35	g/m².day	BS EN 1931
Water tightness at 2kPa	PASS	-	-	-	BS EN 1928

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. The product stated at point 1 conforms to declared performances at point 7.

Adrian Chisholm, Managing Director

.....01.12.2022....

Date

Adrian Chisholm, Managing Director Novia Ltd, Sittingbourne, Kent, UK