

DOP Number: L/500FRPoly/001

CE

1. Unique identification code of the product-type:

Novia 500g FR Virgin Polythene

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:

Flexible sheets for waterproofing - Plastic and rubber vapour control layers according to EN 13894

3. Name and contact address of the manufacturer:

Novia Ltd Unit 3 Trilogy Eurolink V Industrial Park Sittingbourne Kent ME10 3NH

4. System of assessment and verification of constancy of performance of the construction product: System 3; System 1 for Flame Resistance

5. Approved body:

1301 Technický a skúšobný ústav stavebný; 1391 PAVUS Fire Testing Institute

6. Declared Performance:

Essential Characteristics	Specified Value	Unit	Test standard
Tensile strength MD / CD	>16 / >16	N/mm²	EN 12311-2
Maximum elongation at tensile strength MD / CD	>600 / >600	%	EN 12311-2
Resistance to tearing MD / CD	>50 / >50	N	EN 12310-1
Water vapour transmission properties sd	100 (-20/+20)	m	EN 1931
Durability against artificial ageing	Pass		EN 1296 and EN 1931
Reaction to fire	B-s1,d0*	Class	EN 13501-1
Water tightness at 2kPa	Pass		EN 1928

^{*}Valid for substrates with fire class A2-s1, d0 or A1 with density of at least 515kg/m³ with no cavity between product and substrate.

7. The performance of the product according to product (1) corresponds to the declared performances under section 6 and conforms to harmonised standard under section 2.

Adrian Chisholm, Managing Director Date

Novia Limited, Sittingbourne, Kent. UK