



Declaration of Performance

DOP Number: V/500gVirginPoly/002



1. Unique identification code of the product-type:

Novia 500 Gauge VirginPoly – Batch code available on product

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:

For water vapour control layers in buildings according to EN 13984

3. Name and contact address of the manufacturer:

Novia Ltd
Unit 3 Trilogy
Eurolink V Industrial Park
Sittingbourne
Kent
ME10 3NH

4. System of assessment and verification of constancy of performance of the construction product:

System 3


5. Approved body:

KIWA Netherlands 1640

6. Declared Performance:

Essential Characteristics	Specified Value	Unit	Harmonised Standard
Thickness	125 (+/- 12%)	micron	EN 13984:2013
Width	2.7 (+/- 2.5%)	m	
Length	50 (-2% / +10%)	m	
Tensile strength MD:CD	≥13 : ≥13	N/mm ²	
Maximum elongation at tensile strength MD:CD	≥400 : ≥400	%	
Resistance to Impact	≥200	mm	
Water vapour transmission properties in sd	75 (+/- 20%)	m	
Water tightness	PASS		
Water tightness artificial ageing	PASS		

- 7.** The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in according with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


.....
Adrian Chisholm, Managing Director
Novia Limited, Sittingbourne, Kent. UK

.....01.07.2026....
Date