



Declaration of Performance
Number: L/Black115/001

1. Unique identification code of the product-type:

Novia Black 115gsm – (Batch code on product label)

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Underlays for discontinuous roofing according to EN 13859-1 : 2010 and underlays for walls to EN 13859-2 : 2010

3. Name and contact address of the manufacturer:

Novia Ltd
Unit 12 Heronden Road
Park Wood Industrial Estate
Maidstone
Kent
ME15 9YR

4. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2:

N/A

5. System of assessment and verification of constancy of performance of the construction product:

System 3

6. Notified body:

Technicky A Skusobny Ustav Stavebny n.o. Notified Body 1301 performed the initial type test according to EN 13859-1 :2014


7. Declared Performance:

Essential characteristics	Specified Value	Bottom tolerance	Top tolerance	Unit	Test Standard
Length	50	50	51	m	EN1848-2
Width	1500	1493	1523	mm	EN1848-2
Mass per unit area (weight)	116	112.7	127.4	g/m ²	EN1849-2
Tensile strength (MD)	250	200	350	N/50mm	EN12311-1
Tensile strength (CD)	170	135	240	N/50mm	EN12311-1
Max elongation at tensile strength (MD)	60	30	120	%	EN12311-1
Max elongation at tensile strength (CD)	80	40	150	%	EN12311-1
Nail tear resistance (MD)	150	100	200	N	EN12310-1
Nail tear resistance (CD)	190	140	240	N	EN12310-1

Novia®

Resistance to water penetration	W1			Class	EN1928
Water vapour transmission properties sd	0.050	0.020	0.090	m	EN1931/ EN ISO 12572
Reaction to Fire	E			Class	EN13501-1
Dimensional Stability (MD)	-1.3	-2.0	2.0	%	EN1107-2
Dimensional stability (CD)	0.9	-2.0	2.0	%	EN1107-2
Tensile strength after ageing (MD)	235	159	285	N/50mm	EN12311-1
Tensile strength after ageing (CD)	115	81	165	N/50mm	EN12311-1
Elongation after ageing (MD)	40	20	80	%	EN12311-1
Elongation after ageing (CD)	43	20	80	%	EN12311-1
Resistance to water penetration after ageing	W1			Class	EN1928
Flexibility at low temperature	-40	-40	-40	°C	EN 1109
Resistance against air penetration	0.00	0.00	0.00	m ³ /(m ² *h*50PA)	EN 12114

8. The performance of the product according to point no.1 corresponds to the declared performances under section 7.



.....
 Adrian Chisholm, Managing Director
 Novia Ltd, Maidstone, Kent, UK

.....05.03.2019.....
 Date